Page 1 Date SDS Printed & Reviewed: 11/24/15 Last Formula Revision Date: 07/23/15 (APF)

SECTION 1: IDENTIFICATION

PRODUCT IDENTIFIER:

CAA - Aerosol Activator

OTHER MEANS OF IDENTIFICATION (FOR CHEMTREC): FORMULA # 30N027N10

RECOMMENDED USE OF THE CHEMICAL: AEROSOL SPRAY

SUPPLIER DETAILS: MANUFACTURED BY:

MANUFACTURED FOR:

PREMIER PACKAGING CORPORATION 9424 GULFSTREAM ROAD FRANKFORT, IL 60423 815-469-7951 815-469-8047 fax

EMERGENCY 24-HOUR TELEPHONE NUMBERS:

Call CHEMTREC: within USA dial 1-800-424-9300 or outside USA dial +1-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

HAZARD PICTOGRAMS:









GHS02 Flame, GHS04 Gas Cylinder, GHS07 Exclamation Mark, GHS08 Health Hazard

CLASSIFICATION OF THE SUBSTANCE OF MIXTURE:

Flammable Aerosols, Category 1 Gasses Under Pressure, Category Compressed Liquid Skin Corrosion/Irritation, Category 1
Skin Corrosion/Irritation, Category 2
Specific Target Organ Toxicity - Single Exposure, Category 3 Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 1%

SIGNAL WORD: DANGER

HAZARD STATEMENTS:

- H222 Extremely flammable aerosol.
- H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation.

- H336 May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS:

GENERAL & PREVENTION:

- P102 Keep out of reach of children.
- P210 Keep away from heat/sparks/open flames/other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.

- P261
- Avoid breathing vapor/spray.
 Wash hands thoroughly after handling P264
- P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection. **RESPONSE:**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P304+P340 IF INHALED: Remove victim to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P331 Do NOT induce vomiting.

STORAGE:

P403+P233 Store in a well-ventilated place. Keep container tightly closed when not in use.
P410+P403 Protect from sunlight. Store in a well-ventilated place.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 degrees C/122 degrees F. DISPOSAL:

P501 Dispose of contents/container in accordance with local/regional/national regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| # | COMPONENT | CAS# | % by WT. |
|---|-----------|------------|----------|
| 1 | HEPTANE | 64742-49-0 | 70-81 |

SAFETY DATA SHEET Per OSHA HCS

PRODUCT IDENTIFIER:

CAA

ACTIVATOR

15-21 PROPANE 74-98-6 106-97-8 5-8 3 N-BUTANE

SECTION 4 - FIRST AID MEASURES

Inhalation: If inhaled: Move person to fresh air and keep in comfortable position for breathing.

If breathing difficulty persists: Get medical advice/attention.

Skin Contact: If on skin: Wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. If skin irritation persists: Get medical advice/attention.

Eye Contact: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If swallowed: Immediately calls a poison center/doctor. Do NOT induce venition upless directed to

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting unless directed to Ingestion:

do so by medical personnel.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

See Section 11: Toxicological Information and effects.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT REQUIRED:

Treat symptomatically.

SECTION 5 - FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: CO2 (Carbon Dioxide), dry chemical, or water fog.
Unsuitable Extinguishing Media: Water spray may be unsuitable. However if water is used fog nozzles are preferable.

Water may be used to cool closed containers to prevent pressure build-up and explosion when exposed to extreme heat.

Specific Hazards Arising From the Chemical: Closed containers exposed to heat from fire may build pressure and explode. Products of combustion may include but are not limited to: oxides of carbon.

Special Protective Equipment and Precautions for Fire-Fighters: Full protective equipment including

self-contained breathing apparatus should be used.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Environmental Precautions: Prevent contamination of soil/ground, waterways, drains, and sewers. Methods of Containment: Absorb spilled liquid in suitable material. Methods for Clean-Up: Use spark-proof tools to sweep or scrape up, containerize, and dispose of properly. Other Information: Ensure adequate ventilation.

SECTION 7 - HANDLING AND STORAGE

Precautions for Safe Handling:

Vapors may ignite explosively. Prevent buildup of vapors. Keep from sparks, heat, flame or other heat sources. Do not smoke. Turn off pilot lights, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not puncture or incinerate/burn container. Keep container tightly closed while not in use. Conditions for Safe Storage, Including Any Incompatibilities:

Store in dry, well-ventilated area and in accordance with federal, state, and local regulations. Do not expose to heat or store at temperatures above 50 degrees C / 122 degrees F. If storing in cold temperatures, allow product to warm to room temperature before use. Keep container tightly closed and away from heat and sunlight when not in use.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

| # COMPONENT | ACGIH TLV-STEL | ACGIH TLV-TWA | OSHA PEL-TWA |
|-------------|----------------|---------------|--------------|
| 1 HEPTANE | 500 ppm | 400 ppm | 500 ppm |
| 2 PROPANE | 1800 ppm | 2500 ppm | 1000 ppm |
| 3 N-BUTANE | N/E | 800 ppm | 800 ppm |

APPROPRIATE ENGINEERING CONTROLS: Provide adequate ventilation to keep air contamination below OSHA permissible exposure limits and ACGIH TLV exposure levels.

EYE/FACE PROTECTION: Wear safety glasses with side shields. Have eye wash facilities immediately available.

SKIN PROTECTION: Wear chemical resistant gloves if contact is likely.
RESPIRATORY PROTECTION: Use NIOSH-approved air-purifying respirator with organic cartridge or canister if exposure cannot be controlled within applicable limits with ventilation.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Aerosol - Pressurized Liquid COLOR: See product identification

ODOR: Solvent Odor ODOR THRESHOLD: No data available No data available :Hq

FREEZING POINT: Not Established (mixture)

BOILING POINT: Not Applicable (pressurized mixture)

less than -18 degrees C (less than -0.4 degrees F), c.c. FLASH POINT:

EVAPORATION RATE: Faster than ether

Not Established (mixture) Not Established (mixture) UPPER FLAMMABILITY LIMIT: LOWER FLAMMABILITY LIMIT:

SAFETY DATA SHEET Per OSHA HCS

PRODUCT IDENTIFIER:

CAA

ACTIVATOR

VAPOR PRESSURE: Not Established (pressurized mixture)

SPECIFIC GRAVITY: 0.649

SOLUBILITY (WATER): Negligible VOC PERCENT BY WEIGHT: 99.99

HAPS PERCENT BY WEIGHT: Ω

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable under normal conditions.
POSSIBILITY OF HAZARDOUS REACTIONS: Will not occur.
CONDITIONS TO AVOID: Keep away from heat, sparks, and flames.
INCOMPATIBLE MATERIALS: Strong oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS: by fire - Carbon Dioxide and Carbon Monoxide

SECTION 11: TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF ENTRY: Skin contact, Inhalation, Eye contact, Ingestion SIGNS AND SYMPTOMS OF EXPOSURE:

Skin Contact:
Inhalation:
Eye Contact:
Signs/symptoms may include localized redness, itching, drying and cracking of skin.
Intentional concentration and inhalation may be harmful or fatal.
Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the

cornea, and impaired vision.

Central nervous system, kidneys, lungs, liver, eyes, skin, brain, respiratory tract, urinary tract, reproductive system, cardiovascular system

TOXICOLOGICAL DATA:

| # | COMPONENT | LD50 ORAL | LD50 DERMAL | LC50 INHALATION |
|----|-----------|-------------------|----------------------|----------------------|
| 1. | HEPTANE | >5000 mg/kg (rat) | >2000 mg/kg (rabbit) | >73.5 mg/L (rat) 4 h |
| 2. | PROPANE | 1000 | 1800 | N/E |
| 3. | N-BUTANE | N/E | N/E | N/E |

SECTION 12: ECOLOGICAL INFORMATION

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of container and its contents in accordance with federal, state, and local regulations. Do not puncture, incinerate, or place container in trash compactor.

SECTION 14: TRANSPORTATION INFORMATION

GROUND (D.O.T./49 CFR):

UN I.D. Number: UN1950 Transport Hazard Class: 2.1 Packing Group: - (not applicable)

AEROSOLS (",FLAMMABLE" is optional to add after AEROSOLS) Proper Shipping Name:

Hazard label: Limited Quantity (LTD QTY) label -- see 49 CFR 172.315

UN1950, AEROSOLS, 2.1, LTD QTY (can add ",FLAMMABLE" after AEROSOLS) Shipping papers format:

AIR (IATA):

UN I.D. Number: UN1950 Transport Hazard Class: 2.1 Packing Group: - (not applicable)

Proper Shipping Name: AEROSOLS, FLAMMABLE Packing Instruction: Y203

LTD QTY label with "Y" in it, and Flammable Gas label UN1950, AEROSOLS, FLAMMABLE, 2.1 (Note LTD QTY not needed on papers) Hazard labels:

Shipping papers format:

WATER (IMDG):

Packing Group: - (not applicable) UN1950 Transport Hazard Class: 2.1 UN I.D. Number:

Proper Shipping Name: AEROSOLS Hazard label: LTD QTY label (see IMDG 3.4.5.1)

Packing Instruction: P003,LP02 EmS: F-D,S-U Stowage and Segregation: Category A

UN1950, AEROSOLS, 2.1, (-18 C c.c.), LTD QTY Shipping papers format:

No component of this product is a listed Marine Pollutant (49 CFR 172,101,Appendix B).

SECTION 15: REGULATORY INFORMATION

International Chemical Inventory

All components of this product are listed on or exempt from the following inventories: TSCA (United States), CEPA/DSL (Canada), AICS (Australia), IECSC (China)

SECTION 16: OTHER INFORMATION

REVISION DATE: 07/23/15

HMIS & NFPA Hazard Scale:

0=minimal, 1=slight, 2=moderate, 3=serious, 4=severe

SAFETY DATA SHEET Per OSHA HCS

PRODUCT IDENTIFIER:

CAA ACTIVATOR

This SDS is based on information believed to be reliable and accurate. Because of changing reporting requirements and other variables it is impossible to guarantee with complete accuracy all the information contained in this document. It is the responsibility of the user to determine proper personal protection based on actual condition of use and to comply with all federal, state, and local laws and regulations.